

**In the Claims:**

1. (Currently Amended) A circuit testing system, for testing a circuit under test with logic circuits and a scan chain comprising flip-flop cells with inputs and outputs operationally connected to the logic circuits, the circuit under test including a plurality of clock domains, each containing a respective part of the flip-flop cells that are clocked by a respective domain clock signal, the circuit testing system comprising:

a test controller arranged to switch the circuit under test to a test mode wherein the test controller supplies successive test input patterns through the scan chain, each test input pattern being associated with a respective combination of domain clock signals that are selectively enabled to capture a response of the logic circuits to the test input pattern into flip-flop cells of the scan chain, the test controller using the captured response from at least part of the flip-flop cells to detect faults in the circuit under test;

a test pattern selector arranged to select a set of test input patterns and the associated combinations of domain clock signals for use by the test controller, wherein a particular test pattern in the selected set ~~that~~ has the properties that, when the particular test pattern is applied by the test controller:

the response to the particular test pattern captured by a timing sensitive flip-flop cell in a first clock domain is indicative of ~~used to detect~~ a fault condition,

the timing sensitive flip-flop cell receives data dependent on data from a source flip-flop cell that operates on ~~belongs to~~ a second clock domain different from the first clock domain,

the combination of selectively enabled domain clock signals for ~~associated with~~ the particular test pattern comprises the clocks of both the first and second domain, and

~~also has the further property that~~ the data value in the source flip-flop cell is identical to a response value captured by the source flip-flop cell for the particular test pattern.

2. (Previously presented) The circuit testing system according to claim 1, wherein the test pattern selector:

stores information representing an original design that corresponds to the circuit under test;

includes, with each test pattern, clock status signals that indicate whether respective ones of the domain clocks must be disabled during capture of a response to the test pattern;

generates an adapted version of the original design, wherein additional logic circuits have been added to the original design, the additional logic circuits being designed to selectively enable a dependence of an input signal of the timing sensitive flip-flop cell on data from the source flip-flop according to the original design, when the clock status signals indicate that the second domain clock is disabled, the additional circuits also enabling the dependence when the input and output signals of the source flip-flop cell are identical and the second domain clock is enabled;

uses the adapted version to select the test patterns with associated clock status signals so that a set of logic circuit faults is covered for the adapted version.

3. (Currently Amended) A method of testing a circuit under test with logic circuits and a scan chain comprising flip-flop cells with inputs and outputs operationally connected to the logic circuits, the circuit under test comprising a plurality of clock domains, each containing a respective part of the flip-flop cells that are clocked by a respective domain clock signal; the method comprising:

selecting a set of test input patterns each with an associated combination of domain clock signals that will be selectively enabled to capture a response to the test pattern, wherein the set contains a particular test pattern that has the properties that, when the particular test pattern is applied:

the response to the particular test pattern captured by a timing sensitive flip-flop cell in a first clock domain is indicative of ~~used to detect~~ a fault,

the timing sensitive flip-flop cell receives data dependent on data from a source flip-flop cell that operates on ~~belongs to~~ a second clock domain different from the first clock domain,

the combination of selectively enabled domain clock signals for ~~associated with~~ the particular test pattern comprises the clocks of both the first and second domain, and

~~the particular test pattern also having the further property that~~ the data value in the source flip-flop cell is identical to a response value captured by the source flip-flop cell for the particular test pattern;

switching the circuit under test to a test mode,  
supplying successive test input patterns from said set through the scan chain,  
including the particular test pattern;

selectively enabling the combination of domain clock signals for ~~associated with~~ each test pattern to capture a response of the logic circuits to the test pattern into flip-flop cells of the scan chain,

using the captured response from at least part of the flip-flop cells to detect faults in the circuit under test, including the response captured by the timing sensitive flip-flop cell in response to the particular test pattern.

4. (Previously presented) The method of testing according to claim 3, wherein the step of selecting the set of test patterns comprises:

receiving information representing an original design that corresponds to the circuit under test;

including with each pattern clock status signals that indicate whether respective ones of the domain clocks will be disabled during capture of a response to the pattern;

generating an adapted version of the original design wherein additional logic circuits have been added to the original design, the additional logic circuits being designed to selectively enable a dependence of an input signal of the timing sensitive flip-flop cell on data from the source flip-flop cell according to the original design, when the clock status signals indicate that the second

domain clock is disabled, the additional circuits also being designed to enable the dependence when the input and output signals of the source flip-flop cell are identical and the second domain clock is enabled;

selecting the set of test patterns with associated clock status signals for the adapted version so that a set of logic circuit faults is covered for the adapted version.

5. (Previously presented) The method of testing according to claim 4, comprising: tracing back from the input of the timing sensitive flip-flop cell through the logic circuits in the original design until a circuit node is encountered at which node signals depend on the data from the source flip-flop cell but not on any data from flip-flop cells outside the first and second clock domain; said generating including adding an additional gate in the adapted version of the design at said circuit node to realize said selectively enabled dependence.

6. (Currently Amended) A medium carrying a set of test patterns for testing a circuit under test with logic circuits and a scan chain comprising flip-flop cells with inputs and outputs operationally connected to the logic circuits, the circuit under test including a plurality of clock domains, each containing a respective part of the flip-flop cells that are clocked by a respective domain clock signal; each of the set of test input patterns being associated with an associated combination of domain clock signals that will be selectively enabled to capture a response to the test pattern, wherein the set contains a particular test pattern that has the properties that, when the particular test pattern is applied:

the response to the particular test pattern captured by a timing sensitive flip-flop cell in a first clock domain is indicative of ~~used to detect~~ a fault,

the timing sensitive flip-flop cell receives data dependent on data from a source flip-flop cell that operates on ~~belongs to~~ a second clock domain different from the first clock domain,

the combination of selectively enabled domain clock signals for ~~associated with~~ the particular test pattern comprises the clocks of both the first and second domain, and

~~the particular test pattern also having the further property that the data value in the~~  
source flip-flop cell is identical to a response value captured by the source flip-flop cell  
for the particular test pattern.

7. (Previously presented) A method of generating a set of test patterns for a circuit under test with logic circuits and a scan chain comprising flip-flop cells with inputs and outputs operationally connected to the logic circuits, the circuit under test including a plurality of clock domains, each containing a respective part of the flip-flop cells that are clocked by a respective domain clock signal; each test pattern being an associated combination of domain clock signals that will be selectively enabled to capture a response to the test pattern, the method comprising:

receiving information representing an original design that corresponds to the  
circuit under test;

including with each pattern clock status signals that indicate whether respective  
ones of the domain clocks will be disabled during capture of a response to the  
pattern;

generating an adapted version of the original design wherein additional logic  
circuits have been added to the original design, the additional logic circuits  
being designed to selectively enable a dependence of an input signal of the  
timing sensitive flip-flop cell on data from the source flip-flop cell according  
to the original design, when the clock status signals indicate that the second  
domain clock is disabled, the additional circuits also being designed to enable  
the dependence when the input and output signals of the source flip-flop cell  
are identical and the second domain clock is enabled;

selecting the set of test patterns with associated clock status signals for the  
adapted version so that a set of logic circuit faults is covered for the adapted  
version.

8. (Previously presented) A method generating a set of test patterns according to  
claim 7, the method comprising:

tracing back from the input of the timing sensitive flip-flop cell through the logic

circuits in the original design until a circuit node is encountered at which node signals depend on the data from the source flip-flop cell but not on any data from flip-flop cells outside the first and second clock domain;  
said generating including adding an additional gate in the adapted version of the design at said circuit node to realize said selectively enabled dependence.

9. (Previously presented) A test pattern generating machine for generating a set of test patterns for a circuit under test with logic circuits and a scan chain comprising flip-flop cells with inputs and outputs operationally connected to the logic circuits, the circuit under test comprising a plurality of clock domains, each containing a respective part of the flip-flop cells that are clocked by a respective domain clock signal; each test pattern being an associated combination of domain clock signals that will be selectively enabled to capture a response to the test pattern, the machine being arranged to:

receive information representing an original design that corresponds to the circuit under test;

include with each pattern clock status signals that indicate whether respective ones of the domain clocks will be disabled during capture of a response to the pattern;

generating an adapted version of the original design wherein additional logic circuits have been added to the original design, the additional logic circuits being designed to selectively enable a dependence of an input signal of the timing sensitive flip-flop cell on data from the source flip-flop cell according to the original design, when the clock status signals indicate that the second domain clock is disabled, the additional circuits also being designed to enable the dependence when the input and output signals of the source flip-flop cell;

selecting the set of test patterns with associated clock status signals for the adapted version so that a set of logic circuit faults is covered for the adapted version.

10. (Previously presented) A computer program product containing machine instructions for generating a set of test patterns for a circuit under test with logic circuits

and a scan chain comprising flip-flop cells with inputs and outputs operationally connected to the logic circuits, the circuit under test comprising a plurality of clock domains, each containing a respective part of the flip-flop cells that are clocked by a respective domain clock signal; each test pattern being an associated combination of domain clock signals that will be selectively enabled to capture a response to the test pattern, the instructions being arranged to:

- receive information representing an original design that corresponds to the circuit under test; include with each pattern clock status signals that indicate whether respective ones of the domain clocks will be disabled during capture of a response to the pattern;

- generating an adapted version of the original design wherein additional logic circuits have been added to the original design, the additional logic circuits being designed to selectively enable a dependence of an input signal of the timing sensitive flip-flop cell on data from the source flip-flop cell according to the original design, when the clock status signals indicate that the second domain clock is disabled, the additional circuits also being designed to enable the dependence when the input and output signals of the source flip-flop cell are identical and the second domain clock is enabled;

- selecting the set of test patterns with associated clock status signals for the adapted version so that a set of logic circuit faults is covered for the adapted version.